

Push-Pull Units

- Two- and Three-Position
- Non-illuminated

Table 47-187. 2-Position Push-Pull Units — UL (NEMA) Type 3, 3R, 4, 4X, 12, 13

	Operator Position ①		Button Type/Color ②	Push-Pull		Contact Type	Mounting Location	
	Pull	Push		Catalog Number	Price U.S. \$		A	B
								

2-Position Maintained Push, Maintained Pull

	O X	X O	40 mm/Red	10250T5B62-1X		1NO 1NC		
	O X	X O	40 mm Engraved EMERG. STOP/Red	10250T5B63-1X		1NO 1NC		
	O X	X O	65 mm Alum. Engraved EMERG. STOP/Red	10250T5J63-1X		1NO 1NC		
	O X	X O	65 mm Alum. Engraved EMERG. STOP/Red Special Security Jumbo Mushroom Head	10250ED1080-2		1NO 1NC		

Table 47-188. 3-Position Pull-Pull Units — UL (NEMA) Type 3, 3R, 4, 4X, 12, 13

Operator Position ①			Button Type/Color ②	Push-Pull		Contact Type	Mounting Location	
Pull	Intermediate	Push		Catalog Number	Price U.S. \$		A	B
								

3-Position Maintained Push, Momentary Pull

X X	O X	O O	40 mm/ Black	10250T9B60-3X		1NC 1NC		
			40 mm/Red	10250T9B62-3X				
			40 mm Engraved EMERG. STOP/Red	10250T9B63-3X				

3-Position Momentary Push, Momentary Pull

X X	O X	O O	40 mm/Black	10250T4B60-3X		1NC 1NC		
			40 mm/Red	10250T4B62-3X				
O X	O O	X O	40 mm/Black	10250T10B60-1X		1NO 1NC		
			40 mm/Red	10250T10B62-1X				

① X = closed circuit, O = open circuit.

② To order different type or color buttons, substitute the underlined characters with appropriate Suffix Code from the table below.
Example: 10250T5B64-1X.

Table 47-189. Button and Color Selection Table

Standard — 40 mm	Color	Suffix Code	Catalog Number	Price U.S. \$	Jumbo Mushroom Head ③ (Anodized) Aluminum — 65 mm	Color	Suffix Code	Catalog Number	Price U.S. \$
	Red Red (EMERG. STOP) Green Black Blue	B62 B63 B61 B60 B64	10250TB62 10250TB63 10250TB61 10250TB60 10250TB64			Red Red (EMERG. STOP) Green Black Yellow	J62 J63 J61 J60 J64	10250TJ62 10250TJ63 10250TJ61 10250TJ60 10250TJ64	

③ Anodized aluminum head is not suitable for use in ultraviolet light applications.