Industrial Stack Equipment



LEAD COVERED AIR TERMINALS

STAINLESS STEEL AIR TERMINALS



Solid copper air terminals made from high conductivity copper rod with a 1/16" thick lead sheath, tapered point and standard UNC threads.

3/4" Air Terminals

(5/8" thread)

Length

(in)

18

24

36

48

60

72

84

96



Stainless steel air terminals made from 304 grade stainless steel rod, with tapered point and standard UNC threads.

5/8"	Air	Terminals		
(5/8" thread)				

Length

(in)

18

24

36

48

60

72

84

96

3/4" Air Terminals
(5/8" thread)

d)		(5/8" thread)		
	Stainless Steel	Length (in)	Stainless Steel	
	LPS411	18	LPS421	
	LPS412	24	LPS422	
	LPS413	36	LPS423	
	LPS414	48	LPS424	
	LPS415	60	LPS425	
	LPS416	72	LPS426	
	LPS417	84	LPS427	
	LPS418	96	LPS428	

LPLC413 36 48 LPLC414

5/8" Air Terminals

(5/8" thread)

Length

(in)

18

24

60

72 LPLC416 84 LPLC417 96 LPLC418

AIR TERMINAL BASES

Lead-Covered

LPLC411

LPLC412

LPLC415



Series 431





Series 436

Lead-Covered

LPLC421

LPLC422

LPLC423

LPLC424

LPLC425

LPLC426

LPLC427

LPLC428



Current standard requirements specify that side mounted points be anchored at two locations to the structure with the above provided stud counting as one. See page 56 for drop-in anchors for use with the studs. Refer to 480 or 492 series for point holders to be used as the second required anchor.

Part No.	Material	Stud Length (in)
LPC431	Brass	-
LPLC431	Lead Coated Brass	-
LPC433	Brass	-
LPLC433	Lead Coated Brass	-
LPC435SH	Brass	7/8
LPC435LG	Brass	1-1/2
LPLC435SH	Lead Coated Brass	7/8
LPLC435LG	Lead Coated Brass	1-1/2
LPC436SH	Brass	7/8
LPC436LG	Brass	1-1/2
LPLC436SH	Lead Coated Brass	7/8
LPLC436LG	Lead Coated Brass	1-1/2
LPC437SH	Brass	7/8
LPC437LG	Brass	1-1/2
LPLC437SH	Lead Coated Brass	7/8
LPLC437LG	Lead Coated Brass	1-1/2