

PVC Coated Strut Straps

PROCOAT PVC coated strut straps are used with coated strut to support conduit installations in a variety of configurations. Struts straps may be used in either vertical or horizontal positions to support conduit. Both are provided with stainless steel hardware. Conduit spacing may be as close together as allowed by the couplings.

UL: E516500

Features:

- 20 mil gray PVC exterior coating
- Available in 11 trade sizes



Strut Straps

PVC COATED STRUT STRAPS


SIZE	CATALOG #	GAUGE METAL	WEIGHT FOR 100 PCS
1/2"	CL15P	14	13.0
3/4"	CL20P	14	15.0
1"	CL25P	14	17.0
1-1/4"	CL32P	12	19.5
1-1/2"	CL40P	12	28.0
2"	CL50P	12	31.0
2-1/2"	CL65P	12	36.0
3"	CL80P	12	42.0
3-1/2"	CL90P	11	56.0
4"	CL100P	11	64.0
5"	CL125P	10	76.0
6"	CL150P	10	92.0

PVC Coated Ferrous Struts

PROCOAT PVC coated strut is a versatile system of structural elements that can be used to build supports for a variety of applications. When combined with coated conduit hangers and other accessories, coated strut is a versatile and economical way to provide reliable support for conduit runs and other electrical and mechanical installations.

Features:

- 20 mil gray PVC exterior coating
- 2 trade sizes and 3 standard styles



PVC COATED STRUT

CATALOG #	DESCRIPTION	NOMINAL WT. PER 100 FT.	X mm	Y mm	STRUT THICKNESS
A12P	CHANNEL	200	41.3	41.3	12 ga.
A12PP	SLOTTED	185	41.3	41.3	12 ga.
A12AP	DOUBLE CHANNEL	380	41.3	82.5	12 ga.
C14P	SHALLOW	135	41.3	20.6	12 ga.
C14PP	SHALLOW SLOTTED	130	41.3	20.6	12 ga.

PVC Coated Strut Nuts

PROCOAT PVC coated strut nuts are used to assemble strut components and to secure coated all thread rod in a section of strut. These are available with or without a spring to aid in placement and assembly.

Features:

- 20 mil gray PVC exterior coating
- 10 trade sizes from 1/2" through 4"



COATED STRUT NUT

PIPE SIZE	CATALOG #
1/4"	FNS25P
3/8"	FNS38P
1/2"	FNS50P