

MISCELLANEOUS

Sealing Gaskets with Self Retaining Neoprene Rubber Gaskets

Application:

To form a rain tight seal between a conduit fitting and the outside of a box.

Features:

- Neoprene rubber gasket
- Steel retaining ring
- Stainless Steel retaining ring

Standard Materials:

Rubber gaskets
Steel rings


Standard Finish:

Zinc plated

Applicable Third Party


Standards:

UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB-1



Sealing Gaskets with Steel Retaining Ring

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
SG-50	1/2"	1-1/8"	13/16"	3/16"	1000	1.3
SG-75	3/4"	1-3/8"	1-1/8"	3/16"	500	1.5
SG-100	1"	1-5/8"	1-5/16"	3/16"	500	1.9
SG-125	1-1/4"	2"	1-5/8"	3/16"	250	2.5
SG-150	1-1/2"	2-1/4"	1-7/8"	3/16"	200	2.6
SG-200	2"	2-3/4"	2-5/16"	3/16"	200	3.1
SG-250	2-1/2"	3-1/2"	2-7/8"	3/16"	100	6.3
SG-300	3"	4-1/4"	3-1/2"	3/16"	50	9.4
SG-350	3-1/2"	4-3/4"	4"	3/16"	50	9.5
SG-400	4"	5-3/16"	4-1/2"	3/16"	50	12.5
SG-500	5"	6-9/16"	5-9/16"	3/16"	50	15.6
SG-600	6"	7-3/4"	6-5/8"	3/16"	50	18.8



Sealing Gaskets with Stainless Steel Retaining Ring

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
SGS-50	1/2"	1-1/8"	13/16"	3/16"	50	1.3
SGS-75	3/4"	1-3/8"	1-1/8"	3/16"	25	1.5
SGS-100	1"	1-5/8"	1-5/16"	3/16"	25	1.9
SGS-125	1-1/4"	2"	1-5/8"	3/16"	5	2.5
SGS-150	1-1/2"	2-1/4"	1-7/8"	3/16"	5	2.6
SGS-200	2"	2-3/4"	2-5/16"	3/16"	5	3.1



^ Not UL Listed