

CONDUIT BODIES

Watertight Rigid Conduit Bodies with Stamped Steel Cover & Neoprene Gasket, Malleable Iron • for Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- NEMA 4 Watertight

Standard Materials:

Malleable iron
Covers - Stamped steel
Gasket - Neoprene rubber

Standard Finish:

Zinc plated
Aluminum enameled

Applicable Third Party Standards:


UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1
NEMA 4

The only Malleable Iron Conduit Bodies Watertight Rated Type NEMA 4.

Protected from dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water and ice build up.


Winner of the 2007 EC&M Product of the Year Competition in the Conduit & Cable Fitting Category!

**PATENT
PENDING**



Threaded T Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	WEIGHT PER C
MT1CG	1/2"	5-3/8"	2-1/16"	1-11/16"	121.8
MT2CG	3/4"	6"	2-1/4"	1-15/16"	152.0
MT3CG	1"	7-1/16"	2-5/8"	2-1/4"	218.1
MT4CG	1-1/4"	9"	2-3/4"	3-1/8"	367.8
MT5CG	1-1/2"	9"	3-1/2"	3-1/8"	404.6
MT6CG	2"	11-1/2"	4-1/8"	3-3/4"	719.3
MT7CG	2-1/2"	15"	5-11/16"	5-3/16"	1371.5
MT8CG	3"	15-1/8"	5-7/8"	5-3/16"	1647.7
MT9CG	3-1/2"	18-1/8"	6-13/16"	5-3/4"	2692.0
MT10CG	4"	18-1/8"	7-3/16"	5-3/4"	2692.0



Threaded TB Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	WEIGHT PER C
MTB1CG	1/2"	5-1/4"	1-3/8"	1-11/16"	99.7
MTB2CG	3/4"	6-1/16"	1-5/8"	2"	134.7
MTB3CG	1"	7-1/8"	1-7/8"	2-1/4"	219.0
MTB4CG	1-1/4"	9-5/16"	2-5/8"	4-1/4"	378.9
MTB5CG	1-1/2"	9-5/16"	2-5/8"	4-1/4"	456.2
MTB6CG	2"	11-13/16"	3-1/4"	4-3/4"	746.9