

# CONDUIT BODIES

## Watertight Rigid Conduit Bodies with Stamped Steel Cover & Neoprene Gasket, Malleable Iron • for Rigid • IMC conduit

### Application:

To provide access to conductors for pulling, splicing and maintenance.

### Features:

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- NEMA 4 Watertight

### Standard Materials:

Malleable iron  
Covers - Stamped steel  
Gasket - Neoprene rubber

### Standard Finish:

Zinc plated  
Aluminum enameled

### Applicable Third Party


Standards:  
UL Standard: 514A  
Fed. Spec. W-C-586D  
NEMA: FB-1  
NEMA 4

**The only Malleable Iron Conduit Bodies Watertight Rated Type NEMA 4.**

**Protected from dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water and ice build up.**


**Winner of the 2007 EC&M Product of the Year Competition in the Conduit & Cable Fitting Category!**

**PATENT PENDING**



Threaded LL Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	WEIGHT PER C
MLL1CG	1/2"	4-11/16"	2-1/16"	1-3/4"	87.6
MLL2CG	3/4"	5-3/8"	2-1/4"	2-1/8"	109.7
MLL3CG	1"	6-3/16"	2-5/8"	2-5/16"	159.8
MLL4CG	1-1/4"	8-1/8"	2-3/4"	3-1/4"	345.7
MLL5CG	1-1/2"	8-1/8"	3-1/2"	3-5/16"	367.8
MLL6CG	2"	10-1/2"	4-1/8"	3-15/16"	553.6
MLL7CG	2-1/2"	13-5/8"	4-11/16"	4-3/4"	1205.7
MLL8CG	3"	13-7/8"	5-7/8"	5-5/8"	1537.2
MLL9CG	3-1/2"	16-1/4"	6-1/8"	6-1/2"	2471.0
MLL10CG	4"	16-1/4"	6-15/16"	6-1/2"	2581.5



Threaded LR Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	WEIGHT PER C
MLR1CG	1/2"	4-11/16"	2-1/16"	1-3/4"	82.3
MLR2CG	3/4"	5-3/8"	2-1/4"	2-1/8"	115.0
MLR3CG	1"	6-3/16"	2-5/8"	2-5/16"	178.2
MLR4CG	1-1/4"	8-1/8"	2-3/4"	3-1/4"	367.8
MLR5CG	1-1/2"	8-1/8"	2-13/16"	3-5/16"	381.6
MLR6CG	2"	10-1/2"	4-7/16"	3-15/16"	682.5
MLR7CG	2-1/2"	13-5/8"	5-3/8"	4-3/4"	1205.7
MLR8CG	3"	13-7/8"	5-7/8"	5-5/8"	1537.2
MLR9CG	3-1/2"	16-1/4"	6-7/8"	6-1/2"	2471.0
MLR10CG	4"	16-5/8"	7-3/16"	6-1/2"	2650.5