

CONDUIT BODIES

Watertight Rigid Conduit Bodies with Stamped Steel Cover & Neoprene Gasket, Malleable Iron • for Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- NEMA 4 Watertight

Standard Materials:

Malleable iron
Covers - Stamped steel
Gasket - Neoprene rubber

Standard Finish:

Zinc plated
Aluminum enameled

Applicable Third Party


Standards:
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1
NEMA 4

The only Malleable Iron Conduit Bodies Watertight Rated Type NEMA 4.

Protected from dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water and ice build up.


Winner of the 2007 EC&M Product of the Year Competition in the Conduit & Cable Fitting Category!

PATENT PENDING



Threaded LB Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	WEIGHT PER C
MLB1CG	1/2"	4-11/16"	1-3/8"	2-7/16"	81.8
MLB2CG	3/4"	5-3/8"	1-5/8"	2-11/16"	111.7
MLB3CG	1"	6-3/16"	1-7/8"	3-1/16"	164.4
MLB4CG	1-1/4"	8-1/8"	2-5/8"	3-1/4"	323.6
MLB5CG	1-1/2"	8-1/8"	2-5/8"	3-5/16"	367.8
MLB6CG	2"	10-1/2"	3-1/4"	5-1/16"	590.4
MLB7CG	2-1/2"	13-5/8"	4-7/16"	6-1/4"	1205.7
MLB8CG	3"	13-7/8"	4-7/16"	6-3/4"	1261.0
MLB9CG	3-1/2"	16-1/4"	5-11/16"	7-3/4"	2139.5
MLB10CG	4"	16-5/8"	5-11/16"	8-1/16"	2250.0



Threaded C Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	WEIGHT PER C
MC1CG	1/2"	5-3/8"	1-3/8"	1-3/4"	109.5
MC2CG	3/4"	6"	1-5/8"	2-1/8"	133.4
MC3CG	1"	7-1/16"	1-7/8"	2-5/16"	191.4
MC4CG	1-1/4"	9"	2-5/8"	3-1/4"	345.7
MC5CG	1-1/2"	9"	2-5/8"	3-5/16"	404.6
MC6CG	2"	11-1/2"	3-1/4"	3-15/16"	608.8
MC7CG	2-1/2"	15"	4-7/16"	4-3/4"	1316.2
MC8CG	3"	15-1/8"	4-7/16"	5-5/8"	1537.2
MC9CG	3-1/2"	18-1/8"	5-11/16"	6-1/2"	2360.5
MC10CG	4"	18-1/8"	5-11/16"	6-1/2"	2471.0