CONDUIT BODIES

Watertight Aluminum Die Cast Threaded Conduit Bodies with Raised Dome Aluminum Cover & Neoprene Gasket For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:

- Tapered threaded hubs NPT
- Suitable for use in concrete
- NEMA 4 Watertight

Standard Materials: Die cast aluminum Copper free

Covers - Stamped aluminum Gasket - Neoprene rubber

Applicable Third Party Standards: UL Standard: 514A Fed. Spec. W-C-586D NEMA: FB-I NEMA 4

The only Aluminum Conduit Bodies Watertight Rated Type NEMA 4.

Protected from dirt, rain, sleet, snow, windblown dust, splashing water, hosedirected water and ice build up.

Winner of the 2007
EC&M Product of
the Year
Competition in the
Conduit & Cable
Fitting Category!

PATENT PENDING



Phone: 954-427-6820


Fax: 954-427-6446



Threaded T Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ATICGCH	1/2"	4-3/4"	2-1/16"	I-3/4"	10	44.5
AT2CGCH	3/4"	5-9/16"	2-1/4"	2-1/16"	10	52.5
AT3CGCH	I"	6-7/16"	2-5/8"	2-5/16"	5	75.0





Threaded TB Conduit Bodies

CATALOG	TRADE	DIM	DIM	DIM	PCS/UNITS	WEIGHT				
NUMBER	SIZE	Α	В	С	PER BOX	PER C				
ATBICGCH	1/2"	4-3/4"	I-3/8"	2-1/2"	10	40.4				
ATB2CGCH	3/4"	5-1/2"	1-9/16"	2-13/16"	10	57.3				
ATB3CGCH	Ι"	6-1/2"	1-13/16"	3-3/16"	5	79.9				

