

CONDUIT BODIES

Watertight Aluminum Die Cast Threaded Conduit Bodies with Raised Dome Aluminum Cover & Neoprene Gasket For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- NEMA 4 Watertight

Standard Materials:

Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

Applicable Third Party


Standards:
UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1
NEMA 4

The only Aluminum Conduit Bodies Watertight Rated Type NEMA 4.

Protected from dirt, rain, sleet, snow, windblown dust, splashing water, hose-directed water and ice build up.


Winner of the 2007 EC&M Product of the Year Competition in the Conduit & Cable Fitting Category!

**PATENT
PENDING**



Threaded LL Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALL1CGCH	1/2"	4-5/16"	2-1/16"	1-3/4"	10	35.8
ALL2CGCH	3/4"	5-1/16"	2-1/4"	2-1/16"	10	51.8
ALL3CGCH	1"	5-7/8"	2-5/8"	2-5/16"	5	66.9



Threaded LR Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALR1CGCH	1/2"	4-5/16"	2-1/16"	1-3/4"	10	34.0
ALR2CGCH	3/4"	5-1/16"	2-1/4"	2-1/16"	10	52.5
ALR3CGCH	1"	5-7/8"	2-5/8"	2-5/16"	5	70.4