

CONDUIT BODIES

Watertight Aluminum Die Cast Threaded Conduit Bodies with Raised Dome Aluminum Cover & Neoprene Gasket For Rigid • IMC conduit

Application:

To provide access to conductors for pulling, splicing and maintenance.

Features:

- Tapered threaded hubs - NPT
- Suitable for use in concrete
- NEMA 4 Watertight

Standard Materials:

Die cast aluminum
Copper free
Covers - Stamped aluminum
Gasket - Neoprene rubber

Applicable Third Party

Standards:


UL Standard: 514A
Fed. Spec. W-C-586D
NEMA: FB-1
NEMA 4

**The only Aluminum
Conduit Bodies
Watertight Rated
Type NEMA 4.**

**Protected from dirt,
rain, sleet, snow,
windblown dust,
splashing water, hose-
directed water and ice
build up.**


**Winner of the 2007
EC&M Product of
the Year
Competition in the
Conduit & Cable
Fitting Category!**

**PATENT
PENDING**



Threaded LB Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
ALB1CGCH	1/2"	4-5/16"	1-5/16"	2-9/16"	10	35.6
ALB2CGCH	3/4"	5-1/16"	1-9/16"	2-7/8"	10	52.2
ALB3CGCH	1"	5-7/8"	1-3/4"	3-3/16"	5	68.0



Threaded C Conduit Bodies

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
AC1CGCH	1/2"	4-11/16"	1-3/8"	1-11/16"	10	32.6
AC2CGCH	3/4"	5-1/2"	1-9/16"	8-11/16"	10	48.1
AC3CGCH	1"	6-7/16"	1-3/4"	2-5/16"	5	68.0