

SCREW ON LIQUIDTIGHT

Straight Connectors for use with Liquidtight Flexible Metallic Conduit Malleable Iron

Features:

- No disassembly required for installation of Screw On Liquidtight
- Tapered threaded male hub - NPT
- Compact, slim diameter
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout & tight bend conduit pop out
- RoHS Compliant

Standard Materials:

Malleable iron
Steel ferrule
Steel locknut

Standard Finish:

Zinc plated

Applicable Third Party


Standards:

UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB-1


**Winner of the
2006 EC&M
Conduit & Cable
Fitting Category!**

UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under NEC 501-4(b), 502-4(a)(2); Class I, Div. 2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2.

**PATENT
PENDING**



CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
LTQ38	3/8"	1/2"	1-1/8"	1/2"	1-1/8"	400	15.4
LTQ50	1/2"	1/2"	1-1/4"	1/2"	1-1/4"	300	17.6
LTQ75	3/4"	3/4"	1-1/4"	1/2"	1-9/16"	180	28.7
LTQ100	1"	1"	1-7/16"	5/8"	1-13/16"	150	39.7
LTQ125	1-1/4"	1-1/4"	1-1/2"	11/16"	2-1/4"	100	55.1
LTQ150	1-1/2"	1-1/2"	1-5/8"	3/4"	2-7/16"	70	70.5
LTQ200	2"	2"	1-3/4"	3/4"	3"	50	99.2



With Insulated Throat

CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	DIM C	PCS/UNITS PER BOX	WEIGHT PER C
LTQ38-IC	3/8"	1/2"	1-1/8"	9/16"	1-1/8"	400	15.6
LTQ50-IC	1/2"	1/2"	1-1/4"	9/16"	1-1/4"	300	17.8
LTQ75-IC	3/4"	3/4"	1-1/4"	9/16"	1-9/16"	180	28.9
LTQ100-IC	1"	1"	1-7/16"	11/16"	1-13/16"	150	40.1
LTQ125-IC	1-1/4"	1-1/4"	1-1/2"	3/4"	2-1/4"	100	55.7
LTQ150-IC	1-1/2"	1-1/2"	1-5/8"	13/16"	2-7/16"	70	71.2
LTQ200-IC	2"	2"	1-3/4"	13/16"	3"	50	100.2



Easy Assembly and Installation



Phone: 954-427-6820
Fax: 954-427-6446

www.steelcomponentsinc.net