

SCREW ON LIQUIDTIGHT

90° Connectors for use with Liquidtight Flexible Metallic Conduit Malleable Iron

Features:

- No disassembly required for installation of Screw On Liquidtight
- Tapered threaded male hub - NPT
- Compact, slim diameter
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout & tight bend conduit pop out
- RoHS Compliant

Standard Materials:

Malleable iron
Steel ferrule
Steel locknut

Standard Finish:

Zinc plated

Applicable Third Party


Standards:

UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB-1


**Winner of the
2006 EC&M
Conduit & Cable
Fitting Category!**

UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under NEC 501-4(b), 502-4(a)(2); Class I, Div. 2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2

**PATENT
PENDING**



CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	DIM C	DIM D	PCS/UNITS PER BOX	WEIGHT PER C
LTQ3890	3/8"	1/2"	1-5/16"	1/2"	1-1/8"	1-5/8"	200	25.4
LTQ5090	1/2"	1/2"	1-7/16"	1/2"	1-1/4"	1-5/8"	180	28.9
LTQ7590	3/4"	3/4"	1-5/8"	1/2"	1-9/16"	1-3/4"	120	44.1
LTQ10090	1"	1"	2-5/16"	5/8"	1-13/16"	2-1/8"	75	74.5



With Insulated Throat

CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	DIM C	DIM D	PCS/UNITS PER BOX	WEIGHT PER C
LTQ3890-IC	3/8"	1/2"	1-5/16"	9/16"	1-1/8"	1-5/8"	200	25.7
LTQ5090-IC	1/2"	1/2"	1-7/16"	9/16"	1-1/4"	1-5/8"	180	29.2
LTQ7590-IC	3/4"	3/4"	1-5/8"	9/16"	1-9/16"	1-3/4"	120	44.6
LTQ10090-IC	1"	1"	2-5/16"	1 1/16"	1-13/16"	2-1/8"	75	75.3

LIQUIDTIGHT FITTINGS



Phone: 954-427-6820
Fax: 954-427-6446

www.steelcomponentsinc.net