

RIGID - IMC

Edge Type and Parallel Conduit Clamps for Rigid Conduit, IMC & EMT

Application:

Designed to secure Rigid conduit, IMC, or EMT across, parallel or perpendicular to beam, channel and angle supports.

Features:

- Easily installed
- Capable of withstanding heavy loads
- RoHS compliant

Standard Materials:


Malleable iron with steel bolts and nuts

Standard Finish:

Malleable iron parts - Hot dip galvanized


Applicable Third Party

Standards:
UL Standard: 2239



Edge Type Conduit Clamps

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	PCS/UNITS PER BOX	WEIGHT PER C
SETC50	1/2"	2-13/16"	2-1/8"	100	76.9
SETC75	3/4"	2-15/16"	2-3/8"	90	80.4
SETC100	1"	3-1/16"	2-5/8"	85	90.1
SETC125	1-1/4"	3-1/16"	3-1/16"	60	99.4
SETC150	1-1/2"	3-15/16"	3-1/4"	50	110.0
SETC200	2"	4-1/2"	4-1/16"	35	166.3
SETC250	2-1/2"	5-1/8"	4-5/8"	30	210.0
SETC300	3"	5-3/4"	5-1/4"	25	231.9



Parallel Conduit Clamps

CATALOG NUMBER	TRADE SIZE	DIM A	DIM B	PCS/UNITS PER BOX	WEIGHT PER C
SPARC50	1/2"	2-7/8"	1-7/16"	130	53.6
SPARC75	3/4"	3-1/16"	1-11/16"	120	60.6
SPARC100	1"	3-1/4"	2"	100	62.2
SPARC125	1-1/4"	3-5/8"	2-1/8"	70	81.6
SPARC150	1-1/2"	3-7/8"	2-3/16"	70	85.3
SPARC200	2"	4-5/8"	2-7/8"	60	102.5
SPARC250	2-1/2"	5-1/4"	3-1/4"	40	126.5
SPARC300	3"	5-7/8"	3-7/8"	30	153.7
SPARC350	3-1/2"	6-5/16"	4-5/16"	26	163.1
SPARC400	4"	6-13/16"	4-13/16"	22	179.4

^ UL Listing not applicable to these sizes