

EMT

Steel Set Screw Connectors for Steel Conduit

Features:

- Pre-set & staked tri-head screws 1/2" thru 2". Hex head screws 2-1/2" thru 4"
- Male hub threads - NPSM
- Steel locknuts
- Heavy steel walls
- Concrete tight when taped
- UL listed for Steel EMT Conduit
- RoHS compliant


Standard Materials:
Steel

Standard Finish:
Zinc plated


Applicable Third Party Standards:
UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB-1

* Furnished with two set screws

^ Indicates UL and CUL Listed for EMT, IMC & Rigid conduit



CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	PCS/UNITS PER BOX	WEIGHT PER C
SC50R	1/2"	1/2"	7/8"	1-1/2"	304	8.6
SC75R	3/4"	3/4"	1-1/8"	1-9/16"	204	12.8
SC100R	1"	1"	1-3/8"	1-13/16"	120	20.2
SC125R	*1-1/4"	1-1/4"	1-3/4"	2-5/16"	80	35.6
SC150R	*1-1/2"	1-1/2"	2"	2-1/4"	54	45.1
SC200R	*2"	2"	2-7/16"	2-3/8"	42	63.6
^SC250R	*2-1/2"	2-1/2"	3-1/8"	3-3/16"	15	130.0
^SC300R	*3"	3"	3-3/4"	3-13/16"	14	140.0
^SC350R	*3-1/2"	3-1/2"	4-1/4"	4-5/16"	11	180.0
^SC400R	*4"	4"	4-3/4"	4-7/8"	7	225.0



With Insulated Throat

CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	PCS/UNITS PER BOX	WEIGHT PER C
SC50-ICR	1/2"	1/2"	7/8"	1-1/2"	304	8.7
SC75-ICR	3/4"	3/4"	1-1/8"	1-9/16"	204	12.9
SC100-ICR	1"	1"	1-3/8"	1-13/16"	120	20.4
SC125-ICR	*1-1/4"	1-1/4"	1-3/4"	2-1/4"	80	36.0
SC150-ICR	*1-1/2"	1-1/2"	2"	2-5/16"	54	45.6
SC200-ICR	*2"	2"	2-7/16"	2-3/8"	42	64.2
^SC250-ICR	*2-1/2"	2-1/2"	3-1/8"	3-3/16"	15	131.3
^SC300-ICR	*3"	3"	3-3/4"	3-13/16"	14	141.4
^SC350-ICR	*3-1/2"	3-1/2"	4-1/4"	4-5/16"	11	181.8
^SC400-ICR	*4"	4"	4-3/4"	4-7/8"	7	227.3

UL US
E200730
1/2" - 2"

UL US
E207875
2-1/2" - 4"

SCI
STEEL COMPONENTS INC.