

CORD GRIP STRAIN RELIEF CONNECTORS

Color-Coded Cord Grip Connectors

Application:

To secure and seal cords or cables entering enclosures or raceways.

Features:

- Neoprene grommet for a moisture proof seal
- Simple installation, cord can be installed without disassembly of the fitting
- Liquidtight/Oiltight/Raintight
- Suitable for NEMA 4 enclosures and other wet locations
- Male tapered thread NPT
- Colored grommet allows for easy identification
- RoHS compliant

Standard Materials:

Steel body
Steel gland nut
Neoprene grommet


Standard Finish:

Zinc plated body, gland nut

Applicable Third Party

Standards:
UL Standard: 514B
Fed. Spec. W-F-406E

Suitable for use in hazardous locations under NEC 501-4(b), 502-4(a), and 503-3(a). For Class I, Div. 2, Class II, Div. 1, 2, and Class III, Div. 1,2.



CATALOG NUMBER	TRADE SIZE	COLOR CODE	CABLE RANGE		DIM A	DIM B	PCS/UNIT PER BOX	WEIGHT PER C
			Min.	Max.				
CG50-250	1/2"	Red	0.15	0.25	1-7/16"	1-1/8"	350	10.0
CG50-350	1/2"	White	0.25	0.35	1-7/16"	1-1/8"	350	10.0
CG50-450	1/2"	Blue	0.35	0.45	1-7/16"	1-1/8"	350	10.0
CG50-560	1/2"	Green	0.45	0.56	1-7/16"	1-1/8"	350	10.0
CG50-650	1/2"	Brown	0.55	0.65	1-7/16"	1-1/8"	350	10.0
CG75-250	3/4"	Red	0.15	0.25	1-1/2"	1-1/4"	240	14.0
CG75-350	3/4"	White	0.25	0.35	1-1/2"	1-1/4"	240	14.0
CG75-450	3/4"	Blue	0.35	0.45	1-1/2"	1-1/4"	240	14.0
CG75-560	3/4"	Green	0.45	0.56	1-1/2"	1-1/4"	240	14.0
CG75-650	3/4"	Brown	0.55	0.65	1-1/2"	1-1/4"	240	14.0
CG75-750	3/4"	Yellow	0.65	0.75	1-11/16"	1-5/16"	240	14.0
CG75-850	3/4"	Purple	0.75	0.85	1-11/16"	1-5/16"	240	14.0
CG100-560	1"	Green	0.45	0.56	1-3/4"	1-1/2"	140	20.0
CG100-650	1"	Brown	0.50	0.65	1-3/4"	1-1/2"	140	20.0
CG100-750	1"	Yellow	0.65	0.75	1-3/4"	1-1/2"	140	20.0
CG100-850	1"	Purple	0.75	0.85	1-3/4"	1-1/2"	140	20.0
CG100-950	1"	Gray	0.85	0.95	1-15/16"	1-5/8"	140	20.0
CG100-1050	1"	Black	0.95	1.05	1-15/16"	1-5/8"	140	20.0
CG125-850	1-1/4"	Purple	0.75	0.85	1-15/16"	1-7/8"	80	40.0
CG125-950	1-1/4"	Gray	0.85	0.95	1-15/16"	1-7/8"	80	40.0
CG125-1050	1-1/4"	Black	0.95	1.05	2-1/16"	2"	80	40.0
CG125-1150	1-1/4"	Orange	1.05	1.15	2-1/16"	2"	80	40.0
CG125-1250	1-1/4"	Red	1.15	1.25	2-1/16"	2"	80	40.0
CG125-1375	1-1/4"	White	1.25	1.375	2-1/16"	2"	80	40.0
CG150-1050	1-1/2"	Black	0.95	1.05	2-1/8"	2-1/4"	60	70.0
CG150-1150	1-1/2"	Orange	1.05	1.15	2-1/8"	2-1/4"	60	70.0
CG150-1250	1-1/2"	Red	1.15	1.25	2-1/8"	2-1/4"	60	70.0
CG150-1375	1-1/2"	White	1.25	1.375	2-1/8"	2-1/4"	60	70.0

This chart is intended for use as a guide only. Whenever possible, exact cord dimensions should be used. Steel Components Inc. assumes no liability for errors, omissions or dimensional changes which may result from changes in design, material or the manufacturing process and which may affect cord and fitting compatibility.