

RIGID - IMC

Malleable Iron Insulated Conduit Bushings 150° for Threaded Rigid Conduit and IMC

Features:

- The plastic liner won't chip, crack, swell or shrink. It resists corrosion, chemicals and temperature extremes.
- RoHS compliant

Standard Materials:

Body - Malleable iron
Insuliner - ULTEM1000 rated at 150° C


Standard Finish:

Body - Zinc plated


Applicable Third Party

Standards:

UL Standard: 514B
Fed. Spec. W-F-408E
NEMA: FB-1



CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	PCS/UNITS PER BOX	WEIGHT PER C
BRC-50	1/2"	1/2"	1-1/16"	1 1/16"	800	5.5
BRC-75	3/4"	3/4"	1-1/4"	1 1/16"	500	8.8
BRC-100	1"	1"	1-5/8"	3/4"	340	13.2
BRC-125	1-1/4"	1-1/4"	2"	13/16"	260	16.5
BRC-150	1-1/2"	1-1/2"	2-5/16"	13/16"	160	20.9
BRC-200	2"	2"	2-3/4"	7/8"	120	25.4
BRC-250	2-1/2"	2-1/2"	3-5/16"	1"	72	50.7
BRC-300	3"	3"	4"	1"	44	66.1
BRC-350	3-1/2"	3-1/2"	4-3/8"	1-1/16"	42	71.7
BRC-400	4"	4"	5-1/16"	1-1/8"	24	102.5
BRC-500	5"	5"	6-1/8"	1-3/16"	18	146.6
BRC-600	6"	6"	7-3/16"	1-3/16"	14	184.1



Malleable Iron Non-Insulated Conduit Bushings for Threaded Rigid Conduit and IMC

CATALOG NUMBER	TRADE SIZE	KO SIZE	DIM A	DIM B	PCS/UNITS PER BOX	WEIGHT PER C
BRCN-50	1/2"	1/2"	1-1/16"	5/8"	800	5.5
BRCN-75	3/4"	3/4"	1-1/4"	5/8"	500	8.7
BRCN-100	1"	1"	1-5/8"	1 1/16"	340	13.1
BRCN-125	1-1/4"	1-1/4"	2"	3/4"	260	16.4
BRCN-150	1-1/2"	1-1/2"	2-5/16"	13/16"	160	20.7
BRCN-200	2"	2"	2-3/4"	7/8"	120	25.2
BRCN-250	2-1/2"	2-1/2"	3-5/16"	1"	72	50.3
BRCN-300	3"	3"	4"	1"	44	65.6
BRCN-350	3-1/2"	3-1/2"	4-3/8"	1-1/16"	42	71.2
BRCN-400	4"	4"	5-1/16"	1-1/8"	24	101.7
BRCN-500	5"	5"	6-1/8"	1-3/16"	18	145.5
BRCN-600	6"	6"	7-3/16"	1-3/16"	14	182.7

PATENTED

